

2002P05893WO

PCT/DE03/01139

Description

Method for electrodynamically braking a rail vehicle

- 5 The invention relates to a method for electrodynamically braking a rail vehicle which is equipped with a drive, the acceleration of the rail vehicle being controlled as a function of its velocity.
- 10 Until now, an electrodynamic brake was frequently not used to the point where the rail vehicle comes to a standstill. It was feared that the braking force at low speeds were subject to large fluctuations which are due in particular to the route (positive or negative
- 15 gradient).

An existing mechanical brake has always been used below a velocity of 2km/h to 7km/h. This has the disadvantage that when the rail vehicle comes to a standstill there

20 is a jolt which is uncomfortable for the passengers.

A velocity-dependent braking deceleration is known from DE 41 07 514 A1. The significant factor here is to achieve a very short braking distance.

25 US 4,270,716 discloses a method for accelerating and braking a rail vehicle in which, in order to avoid a jolting mode of travel, the acceleration, which may also be negative when braking, is controlled in such a

30 way that it is proportional to the square root of the velocity.

The invention is based on the object of specifying an alternative method for electrodynamically braking a

35 rail vehicle which permits safe braking to the point where the vehicle comes to a standstill so that the mechanical brake which causes an undesired jolt

AMENDED SHEET

ART 24 AMEND

is normally not used and as a result is also subject to less wear.

The object is achieved according to the invention in
5 that the acceleration is controlled to a set point acceleration which is proportional to the velocity.

The advantage is obtained that optimum deceleration (negative acceleration) is possible with a simplified
10 control at any velocity of the rail vehicle, even at a very low velocity. It is therefore possible to bring the rail vehicle to a standstill safely solely using the electrodynamic brakes. The electrodynamic brakes operate advantageously without a jolt.

15 The relationship in which the acceleration is plotted as a function of the velocity can be stored as a characteristic curve.

20 The set point acceleration can also be proportional to the velocity for individual sections (route sections or travel time periods) which follow one another. There results a characteristic curve composed of linear sections.

25 During the braking process, the respective current set point acceleration is determined with the characteristic curve from the velocity of the rail vehicle, and the current acceleration is controlled in such a way that it corresponds as far as possible to
30 the set point acceleration.

Influences of the route being traveled on (positive or negative gradient) are compensated by the control of the acceleration.

35

For example, the acceleration can be controlled

AMENDED SHEET
ART 34 AMDE

2002P05893WO

- 2a -

PCT/DE03/01139

indirectly by controlling the torque of the drive of
the rail vehicle. The torque can be controlled
comparatively

ART 34 AMDT
AMENDED SHEET

more easily than with direct control of the acceleration.

In order to control the torque it is possible to use,
5 for example, a PI controller.

For example, during the control process it is possible to provide for the torque always to be kept within predefined limits. These limits are predefined, for
10 example, by the driver.

For example, an additional torque, which is proportional to the set point acceleration, is added to the torque for the sake of pilot control. Here, the proportionality
15 constant is dependent on vehicle values.

This provides the advantage that influences which are due to the design of the vehicle itself are ruled out entirely or largely.
20

The vehicle values are, for example, in particular the vehicle mass, but also the transmission ratio and/or the diameter of the wheels.

25 The instantaneous velocity of the rail vehicle is determined, for example, from the rotational speeds of the drive and/or of an axle.

The set point acceleration is then determined, for
30 example, using the characteristic curve which represents the set point acceleration as a function of the velocity. The set point acceleration is proportional to the velocity here.

35 The instantaneous acceleration is determined, for example, as a first derivative of the velocity which is

AMENDED SHEET

2002P05893WO

- 3a -

PCT/DE03/01139

determined. A direct comparison between the
instantaneous acceleration

ART 34 AMDE

AMENDED SHEET

and the set point acceleration is then possible, and the acceleration can be controlled.

5 The drive of the rail vehicle is generally an asynchronous machine with a pulse - controlled inverter. If the drive has a coupling of an I-n model to a U model of an engine, the acceleration can be controlled particularly satisfactorily to a point where the rail vehicle comes to a standstill.

10

The method according to the invention can be used for a general control of the travel of the rail vehicle. In particular, the method is well suited to braking a rail vehicle to the point where it comes to a standstill without a mechanical brake having to be applied. It is therefore advantageously ensured that the vehicle will stop without a jolt.

20 The method according to the invention for electrodynamically braking a rail vehicle will be explained in more detail with reference to the drawing:

At first the velocity v of the rail vehicle is determined 1. The instantaneous acceleration a_{act} is determined 2 from the velocity value after the first derivative of the velocity profile has been formed.

30 In parallel with this, the set point acceleration a_{step} is determined 3 from the velocity v using a predefined characteristic curve. According to the characteristic curve, the set point acceleration a_{step} is proportional to the velocity v with the proportionality constant k .

Both the instantaneous acceleration a_{act} and the set point acceleration a_{step} are fed to the controller 4 which may be a PI controller. The torque M_R which is

AMENDED SHEET

ART 34 AMDE

2002P05893WO

- 4a -

PCT/DE03/01139

necessary for the desired control of the instantaneous acceleration a_{act} to the set point acceleration a_{step} , for the drive 6, is output at the output of the controller 4.

ART 34 AMDT

AMENDED SHEET

In order to compensate influences due to the rail vehicle itself, an additional torque M_v in addition to the already calculated torque M_R is added before the drive 6 is actuated. This additional torque M_v is determined 5 by the product of the set point acceleration a_{step} and a proportionality constant m , which may be dependent on the vehicle mass, the transmission ratio and/or the diameter of the wheels. 10

The sum of the torques $M_R + M_v$ is fed to the drive 6 where the acceleration a_{act} of the rail vehicle is controlled by means of the torque $M_R + M_v$. 15

The rotational speed n of the drive 6 is used to determine the velocity v of the rail vehicle and is made available by the drive 6 in order to determine the velocity 1. 20

The method described makes it possible to control the acceleration (deceleration) of the rail vehicle in a uniform fashion, in particular to the point where the vehicle comes to a standstill.

ART 34 AMDT

AMENDED SHEET